

XE480WGM

Hydraulic Grabbing Machine



Operating weight
47000kg

Capacity of lotus claw/
clamshell bucket
1/3.5m³

Rated power
222kW/2100rpm

Main parameters

Engine

Engine model	/	Cummins QSL9
Direct injection	/	√
Four strokes	/	√
Water cooled	/	√
Turbocharged	/	√
Air to air intercooler	/	√
Number of cylinders	/	6
Engine output power	kW/rpm	222/2100
Max torque/rotation speed	N.m/rpm	1424/1300
Displacement	L	8.9

Main performance

Traveling speed	km/h	2/5/20
Swing speed	r/min	8
Gradeability	%	35
Ground pressure	kPa	/
Maximum traction force	kN	168
Rated flow of main pump	L/min	2×296
Main safety valve pressure	MPa	34.3/37.3
Travel system pressure	MPa	34.3
Swing system pressure	MPa	/
Pilot system pressure	MPa	3.9

Fluid capacity

Fuel tank capacity	L	650
Hydraulic tank capacity	L	330
Engine oil capacity	L	30

Appearance size

Overall length	mm	12600
Overall width(walkway)	mm	3124(3686)
Overall height	mm	3739
Width of platform	mm	3050
Minimum ground clearance	mm	422
Tail swing radius	mm	3698
Crawler base	mm	3200
Gauge	mm	2562
Overall width of undercarriage	mm	3124
Counterweight Clearance	mm	1646

Cab

Original cab height	mm	3739
Max. height after elevation	mm	6239

Standard

Boom length	mm	8600
Arm length	mm	6000
Max. operating radius	mm	15677
Max. operating height	mm	13794
Max. operating depth	mm	6883
Theoretical load at maximum radius(with working tool)	T	4.7



Construction Equipment & Engineering

Call 1800CRANES

XCMG Material Handler XE480WGM



1800CRANES
(08) 9459 6212

www.ronco.com.au
xcmg@ronco.com.au

More Comfortable and Safer

The new cab with large vision features lower noise, more comfortable operating environment, high-power air conditioner, better cooling effect, integrated control panel, more comfortable operation, and 8-inch display, more fashionable.

Integrated control panel



The mature upper structure design, large area of glass and rounded corners at the structure all improve the operator's vision, and the best view can be obtained from any position in the cab.

Lifting type cab

With a stable hydraulic lifting type cab structure, the driver can operate safely within the best field of vision, thereby improving the handling efficiency



Wide field of vision and safety

The side of the turntable and the top of the cab are equipped with safety warning lights, which can effectively remind the surrounding personnel during operation and improve the safety during operation

Equipped with omni-directional camera

Both the front arm and the rear counterweight can be equipped with a camera, and the camera is equipped under the lifting cab as a standard, allowing the driver to fully experience the surrounding environment of the vehicle in the cab and improve operating safety

Accomplish

Efficient, safe, comfortable and **environmentally friendly** operations.


A variety of accessories can be selected to easily handle various materials.



Lotus claw




Clamshell bucket



Electromagnetic sucker



Log grapple



Lifting hook